


WLS70 Series



Sealed High Output Strip Light

Banner's WLS70 is a very bright LED luminaire that features an even light output and is designed for a wide variety of environments and applications, including but not limited to machine lighting, automation systems, industrial, wet and harsh environments, railcars, inspection, dairy/poultry production, agriculture, parking garages, and other indoor and outdoor spaces.

- Exceptionally efficient for overall energy and cost savings
- Increase worker productivity and ergonomics with bright, high-quality, uniform light
- Sturdy aluminum housing encased in a shatterproof, UV-stabilized, polycarbonate shell
- Daisy chain long runs of AC lights quickly and easily with cascade quick disconnect models
- Dimming standard on all models Reliably detects opaque and transparent objects






Challenge


- Welding creates very fine dust and smoke from burning and melting of metal
- Hydraulic hoses can leak or rupture
- Requires bright, even light output with varying levels of illumination



Solution

- Tubular, sealed, dust & waterproof housing is IP65-rated
- 1350 lumens per foot of evenly light target surfaces with no hot spots
- Dimmable down to 5% for energy efficiency



Specifications



Operating Voltage	12 to 30 V DC (DC models) 100 to 277 V AC (AC models)
Power	9-37 W
LED Lifetime	L70 = 50,000 hours
Efficacy (lm/w)	Up to 146 lumens per watt
Lumens	300 mm = 1350 900 mm = 4050 600 mm = 2700 1200 mm = 5400
Operating Conditions	-40 to +50 °C (-40 to +122 °F)
Environmental Rating	IP65
Impact Rating	IK10
Certifications	 

Accessories

